

TYRE PRESSURE C-TYRES

Rim	Dimension	Load index		Max. axle load [kg]		Single / dual fitment	Tyre pressure [bar] & load capacity per axle [kg]														Recommended pressure at full load [bar]
							S	D	S	D											
		2.5	2.75	3.0	3.25		3.5	3.75	4.0	4.25	4.5	4.75	5.0	5.25	5.5	5.75					
17"	225/55R17C	109		2060		S	1230	1330	1430	1520	1610	1710	1800	1880	1970	2060					4.75
			107		3900	D	2330	2520	2700	2880	3050	3230	3400	3570	3730	3900					4.75
	215/60R17C	109		2060		S	1230	1330	1430	1520	1610	1710	1800	1880	1970	2060					4.75
			107		3900	D	2330	2520	2700	2880	3050	3230	3400	3570	3730	3900					4.75
	225/60R17C	107		1950		S	1410	1520	1630	1740	1850	1950									3.75
			105		3700	D	2680	2890	3100	3300	3500	3700									3.75
16"	235/60R17C	117		2570		S	1420	1530	1640	1750	1860	1960	2070	2170	2270	2370	2470	2570			5.25
			115		4860	D	2680	2900	3110	3310	3510	3710	3910	4100	4300	4490	4670	4860			5.25
	225/70R17C	108		2000		S	1620	1750	1880	2000											3.25
			106		3800	D	3080	3320	3560	3800											3.25
	205/55R16C	98		1500		S	1080	1170	1250	1340	1420	1500									3.75
			96		2840	D	2050	2220	2380	2530	2690	2840									3.75
15"	195/60R16C	99		1550		S	1120	1210	1300	1380	1470	1550									3.75
			97		2920	D	2110	2280	2440	2600	2760	2920									3.75
	205/60R16C	100		1600		S	1160	1250	1340	1430	1510	1600									3.75
			98		3000	D	2170	2340	2510	2680	2840	3000									3.75
	215/60R16C	103		1750		S	1270	1370	1460	1560	1660	1750									3.75
			101		3300	D	2380	2580	2760	2940	3120	3300									3.75
	225/60R16C	101		1650		S	1340	1440	1550	1650											3.25
			99		3100	D	2510	2710	2910	3100											3.25
	225/60R16C	105		1850		S	1340	1440	1550	1650	1750	1850									3.75
			103		3500	D	2540	2740	2920	3120	3320	3500									3.75
	195/65R16C	104		1800		S	1080	1160	1250	1330	1410	1490	1570	1650	1720	1800					4.75
			102		3400	D	2030	2200	2350	2510	2660	2810	2960	3110	3260	3400					4.75
	205/65R16C	107		1950		S	1170	1260	1350	1440	1530	1610	1700	1780	1870	1950					4.75
			105		3700	D	2210	2390	2560	2730	2900	3060	3220	3380	3540	3700					4.75
	205/65R16C	103		1750		S	1270	1370	1460	1560	1660	1750									3.75
	215/65R16C	109		2060		S	1230	1330	1430	1520	1610	1710	1800	1880	1970	2060					4.75
			107		3900	D	2330	2520	2700	2880	3050	3230	3400	3570	3730	3900					4.75
	215/65R16C	106		1900		S	1240	1340	1440	1530	1630	1720	1810	1900							4.25
			104		3600	D	2350	2540	2720	2900	3080	3260	3430	3600							4.25
	225/65R16C	112		2240		S	1340	1450	1550	1650	1750	1850	1950	2050	2150	2240					4.75
			110		4240	D	2540	2740	2940	3130	3320	3510	3700	3880	4060	4240					4.75
	235/65R16C	115		2430		S	1450	1570	1680	1790	1900	2010	2120	2220	2330	2430					4.75
			113		4600	D	2750	2970	3180	3400	3600	3810	4010	4210	4410	4600					4.75
	235/65R16C	121		2900		S	1490	1610	1720	1840	1950	2060	2170	2280	2380	2490	2590	2700	2800	2900	5.75
			119		5440	D	2790	3020	3230	3450	3660	3860	4070	4270	4470	4670	4860	5060	5250	5440	5.75
	215/70R16C	108		2000		S	1450	1560	1670	1780	1890	2000									3.75
			106		3800	D	2750	2970	3180	3390	3600	3800									3.75
	185/75R16C	104		1800		S	1080	1160	1250	1330	1410	1490	1570	1650	1720	1800					4.75
			102		3400	D	2040	2200	2360	2500	2660	2820	2960	3120	3260	3400					4.75
	195/75R16C	107		1950		S	1170	1260	1350	1440	1530	1610	1700	1780	1870	1950					4.75
			105		3700	D	2220	2380	2560	2740	2900	3060	3220	3380	3540	3700					4.75
	195/75R16C	110		2120		S	1170	1260	1350	1440	1530	1620	1710	1790	1870	1960	2040	2120			5.25
			108		4000	D	2210	2380	2560	2730	2890	3060	3220	3380	3540	3690	3850	4000			5.25
	205/75R16C	110		2120		S	1270	1370	1470	1570	1660	1750	1850	1940	2030	2120					4.75
			108		4000	D	2390	2560	2770	2950	3130	3290	3490	3660	3820	4000					4.75
	205/75R16C	113		2300		S	1270	1370	1470	1570	1660	1760	1850	1940	2030	2120	2210	2300			5.25
			111		4360	D	2400	2600	2780	2980	3160	3340	3500	3680	3860	4020	4200	4360			5.25
	215/75R16C	113		2300		S	1380	1490	1590	1700	1800	1900	2000	2100	2200	2300					4.75
			111		4360	D	2600	2820	3020	3220	3420	3600	3800	3980	4180	4360					4.75
	215/75R16C	116		2500		S	1380	1490	1600	1700	1810	1910	2010	2110	2210	2310	2400	2500			5.25
			114		4720	D	2610	2810	3020	3220	3410	3610	3800	3990	4170	4360	4540	4720			5.25
	225/75R16C	118		2640		S	1460	1580	1690	1800	1910	2020	2130	2230	2340	2440	2540	2640			5.25
		116		5000	D	2760	2980	3200	3410	3620	3820	4020	4220	4420	4620	4810	5000			5.25	
225/75R16C	121		2900		S	1490	1610	1720	1840	1950	2060	2170	2280	2380	2490	2590	2700	2800	2900	5.75	
		120		5600	D	2880	3100	3330	3550	3760	3980	4190	4400	4600	4810	5010	5210	5400	5600	5.75	
205R16C	110		2120		S	1320	1430	1530	1630	1730	1830	1930	2030	2120						4.5	
		108		4000	D	2500	2700	2900	3080	3280	3460	3640	3820	4000						4.5	
14"	205/65R15C	102		1700		S	1230	1320	1420	1520	1610	1700									3.75
			100		3200	D	2320	2500	2680	2860	3030	3200									3.75
	215/65R15C	104		1800		S	1300	1400	1510	1610	1700	1800									3.75
			102		3400	D	2460	2660	2840	3040	3220	3400									3.75
	195/70R15C	104		1800		S	1120	1210	1300	1390	1470	1560	1640	1720	1800						4.5
			102		3400	D	2120	2290	2460	2620	2780	2940	3090	3250	3400						4.5
	205/70R15C	106		1900		S	1190	1280	1370	1460	1550	1640	1730	1810	1900						