



TYRE PRESSURE C-TYRES

Rim	Dimension	Load index		Max. axle load [kg]		Single / dual fitment	Tyre pressure [bar] & load capacity per axle [kg]													Recommended pressure at full load [bar]		
							S	D	S	D	2.5	2.75	3.0	3.25	3.5	3.75	4.0	4.25	4.5		4.75	5.0
17"	225/55R17C	109		2060		S	1230	1330	1430	1520	1610	1710	1800	1880	1970	2060						4.75
		107		3900		D	2330	2520	2700	2880	3050	3230	3400	3570	3730	3900						4.75
	215/60R17C	109		2060		S	1230	1330	1430	1520	1610	1710	1800	1880	1970	2060						4.75
		107		3900		D	2330	2520	2700	2880	3050	3230	3400	3570	3730	3900						4.75
	225/60R17C	107		1950		S	1410	1520	1630	1740	1850	1950										3.75
		105		3700		D	2680	2890	3100	3300	3500	3700										3.75
	235/60R17C	117		2570		S	1420	1530	1640	1750	1860	1960	2070	2170	2270	2370	2470	2570				5.25
		115		4860		D	2680	2900	3110	3310	3510	3710	3910	4100	4300	4490	4670	4860				5.25
225/70R17C	108		2000		S	1620	1750	1880	2000												3.25	
	106		3800		D	3080	3320	3560	3800												3.25	
16"	205/55R16C	98		1500		S	1080	1170	1250	1340	1420	1500										3.75
		96		2840		D	2050	2220	2380	2530	2690	2840										3.75
	195/60R16C	99		1550		S	1120	1210	1300	1380	1470	1550										3.75
		97		2920		D	2110	2280	2440	2600	2760	2920										3.75
	205/60R16C	100		1600		S	1160	1250	1340	1430	1510	1600										3.75
		98		3000		D	2170	2340	2510	2680	2840	3000										3.75
	215/60R16C	103		1750		S	1270	1370	1460	1560	1660	1750										3.75
		101		3300		D	2380	2580	2760	2940	3120	3300										3.75
	225/60R16C	101		1650		S	1340	1440	1550	1650												3.25
		99		3100		D	2510	2710	2910	3100												3.25
	225/60R16C	105		1850		S	1340	1440	1550	1650	1750	1850										3.75
		103		3500		D	2540	2740	2920	3120	3320	3500										3.75
	195/65R16C	104		1800		S	1080	1160	1250	1330	1410	1490	1570	1650	1720	1800						4.75
		102		3400		D	2030	2200	2350	2510	2660	2810	2960	3110	3260	3400						4.75
	205/65R16C	107		1950		S	1170	1260	1350	1440	1530	1610	1700	1780	1870	1950						4.75
		105		3700		D	2210	2390	2560	2730	2900	3060	3220	3380	3540	3700						4.75
	205/65R16C	103		1750		S	1270	1370	1460	1560	1660	1750										3.75
	215/65R16C	109		2060		S	1230	1330	1430	1520	1610	1710	1800	1880	1970	2060						4.75
		107		3900		D	2330	2520	2700	2880	3050	3230	3400	3570	3730	3900						4.75
	215/65R16C	106		1900		S	1240	1340	1440	1530	1630	1720	1810	1900								4.25
		104		3600		D	2350	2540	2720	2900	3080	3260	3430	3600								4.25
	225/65R16C	112		2240		S	1340	1450	1550	1650	1750	1850	1950	2050	2150	2240						4.75
		110		4240		D	2540	2740	2940	3130	3320	3510	3700	3880	4060	4240						4.75
	235/65R16C	115		2430		S	1450	1570	1680	1790	1900	2010	2120	2220	2330	2430						4.75
		113		4600		D	2750	2970	3180	3400	3600	3810	4010	4210	4410	4600						4.75
	235/65R16C	121		2900		S	1490	1610	1720	1840	1950	2060	2170	2280	2380	2490	2590	2700	2800	2900		5.75
		119		5440		D	2790	3020	3230	3450	3660	3860	4070	4270	4470	4670	4860	5060	5250	5440		5.75
	215/70R16C	108		2000		S	1450	1560	1670	1780	1890	2000										3.75
		106		3800		D	2750	2970	3180	3390	3600	3800										3.75
	185/75R16C	104		1800		S	1080	1160	1250	1330	1410	1490	1570	1650	1720	1800						4.75
		102		3400		D	2040	2200	2360	2500	2660	2820	2960	3120	3260	3400						4.75
	195/75R16C	107		1950		S	1170	1260	1350	1440	1530	1610	1700	1780	1870	1950						4.75
		105		3700		D	2220	2380	2560	2740	2900	3060	3220	3380	3540	3700						4.75
	195/75R16C	110		2120		S	1170	1260	1350	1440	1530	1620	1710	1790	1870	1960	2040	2120				5.25
		108		4000		D	2210	2380	2560	2730	2890	3060	3220	3380	3540	3690	3850	4000				5.25
	205/75R16C	110		2120		S	1270	1370	1470	1570	1660	1750	1850	1940	2030	2120						4.75
		108		4000		D	2390	2560	2770	2950	3130	3290	3490	3660	3820	4000						4.75
	205/75R16C	113		2300		S	1270	1370	1470	1570	1660	1760	1850	1940	2030	2120	2210	2300				5.25
		111		4360		D	2400	2600	2780	2980	3160	3340	3500	3680	3860	4020	4200	4360				5.25
	215/75R16C	113		2300		S	1380	1490	1590	1700	1800	1900	2000	2100	2200	2300						4.75
		111		4360		D	2600	2820	3020	3220	3420	3600	3800	3980	4180	4360						4.75
	215/75R16C	116		2500		S	1380	1490	1600	1700	1810	1910	2010	2110	2210	2310	2400	2500				5.25
		114		4720		D	2610	2810	3020	3220	3410	3610	3800	3990	4170	4360	4540	4720				5.25
	225/75R16C	118		2640		S	1460	1580	1690	1800	1910	2020	2130	2230	2340	2440	2540	2640				5.25
		116		5000		D	2760	2980	3200	3410	3620	3820	4020	4220	4420	4620	4810	5000				5.25
	225/75R16C	121		2900		S	1490	1610	1720	1840	1950	2060	2170	2280	2380	2490	2590	2700	2800	2900		5.75
		120		5600		D	2880	3100	3330	3550	3760	3980	4190	4400	4600	4810	5010	5210	5400	5600		5.75
	205R16C	110		2120		S	1320	1430	1530	1630	1730	1830	1930	2030	2120							4.5
	108		4000		D	2500	2700	2900	3080	3280	3460	3640	3820	4000							4.5	
15"	205/65R15C	102		1700		S	1230	1320	1420	1520	1610	1700										3.75
		100		3200		D	2320	2500	2680	2860	3030	3200										