

Which Heki Rooflight do I have?

Heki 1



Operation	Handles / Crank
Remote control	no
Positions	5 / variable
Forced ventilation	no
Max. opening angle	70°
12-volt lights	no
Rain sensor	no
Glazing	PMMA double
Blackout	Roller blind system
Frame material	PU foam
Frame colour	RAL 9001
Standard roof thickness	27 mm
Possible roof thickness	28 – 60 mm(Requires shortening of the inner frame)
Space size (W x H)	960 x 655 mm
Weight (approx.)	22.0 kg

Details:

Hinged at the front, bar operation, wind-up or electric motor.
Lights in frame.

Aperture in frame: 790mm x 510mm

Dome Size: 1070mm x 760mm

Cut out required to fit: 960mm x 655mm

Heki 2 & Heki 2 Delux



	Delux	Normal
Operation	Lever	Lever
Positions	3	3
Forced ventilation	yes	yes
Max. opening angle	55°	55°
12-volt lights	4 x 5 W	no
Rain sensor	no	no
Glazing	PMMA double	PMMA double
Blackout	Duette	Roller blind system
Fly screen	Roller blind system	Roller blind system
Frame material	ASA	ASA
Frame colour	RAL 9001	RAL 9001
Standard roof thickness	25 – 32 mm	25 – 32 mm
Possible roof thickness	25 – 60 mm(Requires additional assembly set)	25 – 60 mm(Requires additional assembly set)
Space size (W x H)	960 x 655 mm	1080 x 790 mm
Weight (approx.)	11.0 kg	960 x 655 mm

Details:

Hinged at the front, bar operation, with a gas strut.
Lights in frame.

Aperture in frame: 830mm x 530mm

Dome Size: 1050mm x 750mm

Cut out required to fit: 960mm x 655mm

Heki 3 Plus



Operation	Crank
Positions	variable
Forced ventilation	no
Max. opening angle	70°
12-volt lights	2 x 8 W
Rain sensor	no
Glazing	PMMA double
Blackout	Duette
Fly screen	Single pleating
Frame material	ASA
Frame colour	RAL 9001
Standard roof thickness	25 – 32 mm
Possible roof thickness	25 – 60 mm(Requires additional assembly set)
External space requirement	1080 x 790 mm
Space size (W x H)	960 x 655 mm
Weight (approx.)	15.0 kg
Model	With lighting Without lighting

Details:

Hinged at the front, bar operation, wind-up or electric motor.

Lights in frame.

Aperture in frame: 745mm x 533mm

Dome Size: 1050mm x 750mm

Cut out required to fit: 960mm x 655mm

Heki 4 Plus



Operation	electric
Remote control	yes
Positions	variable
Forced ventilation	no
Max. opening angle	70°
12-volt lights	2 x 8 W
Rain sensor	yes
Glazing	PMMA double
Blackout	Duette
Fly screen	Single pleating
Frame material	ASA
Frame colour	RAL 9001
Standard roof thickness	25 – 32 mm
Possible roof thickness	25 – 60 mm(Requires additional assembly set)
Space size (W x H)	960 x 655 mm
Weight (approx.)	15.5 kg

Details:

Hinged at the front.
Lights in frame.

Aperture in frame: 745mm x 533mm

Dome Size: 1050mm x 750mm

Cut out required to fit: 960mm x 655mm

Mini Heki



Weight	2.9 kg
Dimensions	50 x 40 x 40 cm
Operation	Handles
Remote control	no
Positions	5
Forced ventilation	yes
12-volt lights	no
Rain sensor	no
Glazing	PMMA single
Blackout	Single pleating
Fly screen	Single pleating
Frame material	ASA
Frame colour	RAL 9001
Standard roof thickness	23 – 42or43 – 60 mm
Possible roof thickness	23 – 41 mm 43 – 59 mm
Space size (W x H)	400 x 400 mm
Weight (approx.)	2.9 kg

Details:

Hinged at the front, bar operation, push button release to open.

Aperture in frame: 380mm x 370mm

Dome Size: 535mm x 495mm

Cut out required to fit: 400mm x 400mm

Midi Heki



Operation	Lever / Crank / Electric
Remote control	no
Positions	Lever: 3Crank: variableElectric: variable
Forced ventilation	optional
Max. opening angle	Lever: 45°Crank: 60°Electric: 60°
12-volt lights	no
Rain sensor	no
Glazing	PMMA double
Blackout	Single pleating
Fly screen	Single pleating
Frame material	ASA
Frame colour	RAL 9001
Standard roof thickness	30 – 34 mm
Possible roof thickness	25 – 29 / 35 – 60 mm(Requires additional assembly set)
Space size (W x H)	700 x 500 mm
Weight (approx.)	Lever: 8.0 kg, Crank: 8.5 kg, Electric: 9.0 kg
Model	lever (with forced ventilation) lever (without forced ventilation) crank (with forced ventilation) crank (without forced ventilation) electric (with forced ventilation) electric (without forced ventilation)

Details:

Hinged at the front. Bar operation and wind-up or electric motor.

Aperture in frame: 585mm x 404mm

Dome Size: 858mm x 617mm

Cut out required to fit: 700mm x 500mm